#### **TOWN OF LOS GATOS GENERAL NOTES:**

1. ALL WORK SHALL BE IN ACCORDANCE WITH THESE PLANS AND THE PROJECT SPECIFICATIONS.

2. THE CONTRACTOR SHALL PROCURE FROM THE TOWN AND ALL OTHER APPLICABLE AGENCIES ALL PERMITS AND LICENSES AND PAY ALL PERMIT AND LICENSE

3. CONSTRUCTION SHALL BE ALLOWED ONLY BETWEEN THE HOURS OF 8:00 AM AND 5:00 PM ON WEEKDAYS AND LANE CLOSURES TO BE PER APPROVED TRAFFIC CONTROL PLAN. CONSTRUCTION EQUIPMENT SHALL BE PROPERLY MUFFLED AND MAINTAINED.

4. THE CONTRACTOR SHALL PROTECT EXISTING SURVEY MONUMENTS AND OTHER SURVEY MARKERS DURING CONSTRUCTION. ALL SUCH MONUMENTS OR MARKERS DESTROYED DURING CONSTRUCTION SHALL BE REPLACED IN A LEGAL MANNER AT THE CONTRACTOR'S EXPENSE.

5. THE CONTRACTOR SHALL PREVENT THE FORMATION OF ANY AIRBORNE DUST NUISANCE AND SHALL BE RESPONSIBLE FOR ANY DAMAGE RESULTING FROM

6. THE CONTRACTOR SHALL PROVIDE ALL LIGHTS, SIGNS, BARRICADES, FLAGGERS, TEMPORARY CONSTRUCTION FENCING AROUND PROJECT SITE, AND OTHER DEVICES NECESSARY TO PROVIDE FOR PUBLIC CONVENIENCE AND SAFETY

7. EXISTING UNDERGROUND UTILITIES AND IMPROVEMENT ARE SHOWN IN THEIR APPROXIMATE LOCATIONS BASED UPON RECORD INFORMATION AVAILABLE TO THE ENGINEER AT THE TIME OF PREPARATIONS OF THESE PLANS. NO GUARANTEE IS MADE AS THE THE ACCURACY OR COMPLETENESS OF THE INFORMATION SHOWN. THE CONTRACTOR SHALL NOTIFY UTILITY COMPANIES, AT LEAST 2 WORKING DAYS IN ADVANCE OF CONSTRUCTION, TO FIELD LOCATE UTILITIES. CALL UNDERGROUND SERVICE ALERT (U.S.A.) AT 811. THE CONTRACTOR SHALL DETERMINE THE EXISTENCE AND LOCATION OF UTILITIES SHOWN ON THESE PLANS, INDICATED IN THE FIELD BY LOCATING SERVICES, OR EVIDENCE BY FACILITIES VISIBLE AT OR ADJACENT TO THE JOB SITE. ANY ADDITIONAL COST INCURRED

8. EXISTING UTILITIES AND IMPROVEMENTS DAMAGED DURING CONSTRUCTION OPERATIONS SHALL BE COMPLETELY REPAIRED, REMOVED AND REPLACED, OR RESTORED AS DETERMINED BY THE ENGINEER OR UTILITY COMPANY AT THE CONTRACTOR'S SOLE EXPENSE.

9. ANY RELOCATION OF UTILITIES SHALL BE CONDUCTED IN ACCORDANCE WITH THE REQUIREMENTS OF THE UTILITY COMPANY

10. THE CONTRACTOR SHALL COMPLY WITH CLEAN WATER ACT REGULATIONS AND NPDES PERMIT REQUIREMENTS IN EFFECT AT THE TIME OF CONSTRUCTION.

11. AT LEAST ONE LANE OF TRAFFIC IN EACH DIRECTION SHALL BE OPEN AT ALL TIMES DURING CONSTRUCTION. THE CONTRACTOR SHALL PROVIDE ADEQUATE TRAFFIC CONTROL TO DIRECT TRAFFIC. ANY DEVIATION FROM SAID APPROVED TRAFFIC CONTROL PLAN SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL AT LEAST TEN (10) WORKING DAYS PRIOR TO COMMENCEMENT OF WORK REQUIRING SAID DEVIATION.

THE CONTRACTOR SHALL NOTIFY THE ENGINEER IN WRITING OF THE DATES AND DURATION OF ANY PROPOSED LANE CLOSURE, AT LEAST FIVE (5) WORKING DAYS PRIOR TO SAID CLOSURE. ALL LANES SHALL REMAIN OPEN AT ALL OTHER TIMES.

12. THE CONTRACTOR SHALL CONTACT THE TOWN FIVE (5) WORKING DAYS PRIOR TO ANY ADJUSTMENTS OR RELOCATION OF TOWN FACILITIES.

13. THE CONTRACTOR SHALL PROVIDE AND MAINTAIN PEDESTRIAN ACCESS AND SAFETY AT ALL TIMES.

14. ANY POTENTIAL CONFLICTS OR DISCREPANCIES BETWEEN FIELD CONDITIONS AND THESE PLANS AND THE PROJECT SPECIFICATIONS SHALL IMMEDIATELY BE BROUGHT TO THE ATTENTION OF THE ENGINEER. WORK SHALL NOT PROCEED UNTIL THE CONFLICTS OR DISCREPANCIES ARE RESOLVED BY THE ENGINEER.

15. THE CONTRACTOR SHALL PROVIDE ALL TESTING REQUIRED PER THE SPECIFICATIONS AND SHALL SUBMIT ALL TEST RESULTS TO THE ENGINEER FOR ACCEPTANCE PRIOR TO THE NEXT STAGE OF WORK.

#### TOWN OF LOS GATOS STANDARD CONSTRUCTION NOTES

1. ALL WORK SHALL BE ACCORDING TO PROJECT PLANS AND SPECIFICATIONS.

2. A PRE-JOB MEETING IS REQUIRED WITH THE TOWN ENGINEERING INSPECTOR BEFORE THE START OF ANY CONSTRUCTION WORK (408/395-3430).

3. ALL CONTRACTORS WILL BE RESPONSIBLE FOR VERIFICATION OF LOCATION OF ALL EXISTING UTILITIES IN THE FIELD. LOCATIONS SHOWN ON PLANS ARE APPROXIMATE AND FOR GENERAL INFORMATION ONLY. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY EXISTENCE OF AND PROTECT ALL EXISTING SURFACE AND UNDERGROUND FACILITIES AND TO BARE ANY EXPENSE FOR THE REPAIR OF SUCH FACILITIES.

4. IN PAVED STREETS, ALL TRENCH CUTS SHALL BE SMOOTH AND VERTICAL WITH THE AREA BEING GENERALLY RECTANGULAR.

5. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO PROTECT AND PRESERVE ALL SURVEY MONUMENTS SET OR FOUND. DURING THE CONSTRUCTION OF THIS PROJECT.

6. THE TYPES, LOCATIONS, SIZE AND/OR DEPTHS OF EXISTING UNDERGROUND UTILITIES AS SHOWN ON THESE IMPROVEMENT PLANS. WERE OBTAINED FROM SOURCES OF VARYING RELIABILITY. THE CONTRACTOR IS CAUTIONED THAT ONLY ACTUAL EXCAVATION WILL REVEAL THE TYPES, EXTENT, SIZES, LOCATIONS AND DEPTHS OF SUCH UNDERGROUND UTILITIES. THE CONTRACTOR SHALL CONTACT UNDERGROUND SERVICE ALERT (USA) AT 1 (800) 642-2444 A MINIMUM OF FORTY-EIGHT (48) HOURS BEFORE BEGINNING ANY UNDERGROUND WORK AND SHALL REQUEST THAT ALL UTILITIES WITHIN THE WORK AREA BE LOCATED AND MARKED.


7. CONTRACTOR SHALL ALWAYS KEEP THE ENTIRE JOB SITE IN A NEAT AND DUST FREE CONDITION, WHICH SHALL MEET OR EXCEED THE REQUIREMENTS OF THE APPROPRIATE AIR QUALITY MANAGEMENT AGENCIES, THE TOWN OF LOS GATOS, AND BE TO THE SATISFACTION OF THE TOWN ENGINEER. THIS REQUIREMENT SHALL BE IN EFFECT ON A TWENTY-FOUR (24) HOUR PER DAY, SEVEN (7) DAY PER WEEK BASIS AND SHALL NOT BE LIMITED IN ANY WAY TO THE HOURS OF WORK OF THE PROJECT. IF, AT THE SOLE DISCRETION OF THE TOWN ENGINEER, ADDITIONAL DUST CONTROL MEASURES OR DUST PALLIATIVES ARE DEEMED TO BE REQUIRED, THE CONTRACTOR SHALL, AT HIS/HER SOLE EXPENSE TAKE SUCH MEASURES OR APPLY SUCH PALLIATIVES AS DIRECTED BY THE TOWN ENGINEER. IF THE CONTRACTOR IS DEEMED TO BE NON RESPONSIVE TO THE DIRECTION OF THE TOWN ENGINEER, THE TOWN ENGINEER SHALL HAVE THE AUTHORITY TO TAKE ALL MEASURES REQUIRED TO CORRECT ANY SITUATION WHICH HE/SHE DEEMS TO BE OUT OF COMPLIANCE. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE AND LIABLE, TO THE TOWN OF LOS GATOS, FOR ALL COSTS ASSOCIATED WITH THE ACTIONS TAKEN BY THE TOWN ENGINEER TO CORRECT ANY NON-COMPLIANT SITUATION ARISING FORM THE WORK AREA.

#### AGENCY INDEX

| SANTA CLARA COUNTY FIRE DEPARTMENT       | (408) 378-401                                   |
|--|---|
| CITY OF TOWN OF LOS GATOS - PUBLIC WORKS | (408) 399–577                                   |
| SBC TELEPHONE                            | (408) 493-706                                   |
| PACIFIC GAS & ELECTRIC                   | (408) $725-214$                                 |
| SAN JOSE WATER COMPANY                   | (408) 279-785                                   |
| SANTA CLARA VALLEY WATER DISTRICT        | (408) 265-260<br>(408) 452-910<br>(408) 378-240 |
| COMCAST CABLE TELEVISION                 | (408) 452-910                                   |
| WEST VALLEY SANITATION DISTRICT          | (408) 378 - 240                                 |
|  |   |

## TOWN OF LOS GATOS

WINCHESTER - LARK INTERSECTION IMPROVEMENTS CIP NO. 13-04



| ADDICETIA | (LAISTING)  |
|-----------|---|
| ARV       | AIR RELEASE VALVE   |
| BFP       | BACK FLOW PREVENTER   |
| BL        | BUILDING LINE   |
| BM        | BENCHMARK   |
| BOL       | BOLLARD   |
| CATV      | CABLE TV BOX  |
| CB        | CATCH BASIN   |
| CONC      | CONCRETE SPOT FLEVATIO  |
| COR       | CORNER  |
| CPNT      | CONTROL POINT   |
| DFT       | AIR RELEASE VALVE BACK FLOW PREVENTER BUILDING LINE BENCHMARK BOLLARD CABLE TV BOX CATCH BASIN CONCRETE SPOT ELEVATIO CORNER CONTROL POINT TRAFFIC DETECTOR BOX ELECTRICAL BOX EDGE OF CONCRETE   |
| FROX      | FLECTRICAL BOX  |
| EC        | EDGE OF CONCRETE  |
| EM        | ELECTRICAL METER  |
| EP        | EDGE OF DAVEMENT  |
| ES        | ELECTRICAL SWITCH DANIEL  |
| FDC       | FIRE DEDT CONNECTION  |
| FDC       | FIRE DEPT CONNECTION  |
| FL<br>GND | COOLING COOT FLEWATION  |
| GND       | GROUND SPUT ELEVATION   |
| GV        | GAS VALVE   |
| HVLT      | HIGH VOLTAGE VAULT  |
| HYD       | HYDRANI   |
| ICV       | IRRIGATION CONTROL VALV   |
| JP        | JOINT POLE  |
| LAM       | LIQUID AMBAR  |
| LIP       | LIP OF GUITER   |
| MB        | USPS MAIL BOX   |
| MON       | MONUMENT  |
| PAV       | PAVEMENT SPOT ELEVATION   |
| SLB       | STREET LIGHTING BOX   |
| SSC0      | SANITARY SEWER CLEANOL  |
| SSMH      | SANITARY SEWER MANOLE   |
| STLT      | STREET LIGHT  |
| TBOX      | TELEPHONE BOX   |
| TC        | TOP OF CURB   |
| TSB       | TRAFFIC SIGNAL BOX  |
| TSP       | TRAFFIC SIGNAL POLE   |
| WL        | WATER LINE  |
| WM        | WATER METER   |
| WV        | TRAFFIC DETECTOR BOX ELECTRICAL BOX EDGE OF CONCRETE ELECTRICAL METER EDGE OF PAVEMENT ELECTRICAL SWITCH PANEL FIRE DEPT CONNECTION FLOW LINE GROUND SPOT ELEVATION GAS VALVE HIGH VOLTAGE VAULT HYDRANT IRRIGATION CONTROL VALV JOINT POLE LIQUID AMBAR LIP OF GUTTER USPS MAIL BOX MONUMENT PAVEMENT SPOT ELEVATIO STREET LIGHTING BOX SANITARY SEWER CLEANOL SANITARY SEWER MANOLE STREET LIGHT TELEPHONE BOX TOP OF CURB TRAFFIC SIGNAL BOX TRAFFIC SIGNAL BOX TRAFFIC SIGNAL POLE WATER LINE WATER METER WATER VALVE TRANSFORMER |
| XFMR      | TRANSFORMER   |
|           | 000000000000000000000000000000000000000   |

CROSSWALK SIGNAL POLE

ABBREVIATIONS: (EXISTING)

#### <u>ABBREVIATIONS</u>

MAX MAXIMUM

(ME) MATCH EXISTING ELEVATION

| AB   | AGGREGATE BASE            | МН     | MANHOLE            |
|------|---------------------------|--------|--------------------|
| AC   | ASPHALT CONCRETE          | MIN    | MINIMUM            |
| ACC  | ACCESSIBLE                | O.C.   | ON CENTER          |
| AGG  | AGGREGATE                 | Р      | PAVEMENT SURFACE E |
| BC   | BEGIN CURVE               | ₽      | PROPERTY LINE      |
| BW   | BACK OF WALK ELEVATION    |        |                    |
| CL   | CENTER LINE               |        | PORTLAND CEMENT CO |
| DIA  | DIAMETER                  | PVC    | POLYVINYL CHLORID  |
| DWY  | DRIVEWAY                  |        | RADIUS             |
| (E)  | EXISTING                  | R.C.   | RELATIVE COMPACTI  |
| EC   | END CURVE                 | RIM    |                    |
| EX   | EXISTING                  |        | RIGHT TURN         |
| ELEV | ELEVATION                 | •      | RIGHT-OF-WAY       |
| FG   | THINGIT ON THE            |        | SLOPE              |
| FH   | 1 11 12 11 12 11 11 11 11 |        | STANDARD PLAN NU   |
| FL   | FLOW LINE                 |        | STATION            |
| FL   | FLOW LINE                 |        | STORM DRAIN        |
| GB   |                           |        | STANDARD           |
| HC   | 7.00200.B22               |        | SIDEWALK           |
| INV  |                           |        | TOP OF CURB        |
| L    | LEFT                      |        | TEMPORARY          |
| LF   | LINEAR FEET               |        | TOWN OF LOS GATO   |
| LS   | LANDSCAPE                 | TYP    | TYPICAL            |
|      |                           | \ /T A | VALUEN TO AMODODIA |

| AC<br>ACC<br>AGG<br>BC<br>BW<br>CL<br>DIA<br>DWY<br>(E)<br>EC<br>EX<br>EFG<br>FL<br>GB<br>HC<br>NV | AGGREGATE BEGIN CURVE BACK OF WALK ELEVATION CENTER LINE DIAMETER DRIVEWAY EXISTING END CURVE EXISTING ELEVATION FINISH GRADE FIRE HYDRANT FLOW LINE FLOW LINE | PCC<br>PVC<br>R<br>R.C.<br>RIM<br>RT<br>R/W<br>S=<br>SPN<br>STA<br>SD<br>STD<br>SW<br>TC<br>TEMP<br>TLG | RADIUS RELATIVE COMPACTION RIM ELEVATION RIGHT TURN RIGHT—OF—WAY SLOPE STANDARD PLAN NUMBER STATION STORM DRAIN STANDARD SIDEWALK TOP OF CURB TEMPORARY TOWN OF LOS GATOS |
|--|--|---|---|
|  | LEFT   |   |   |
|  | LINEAR FEET  | TLG   | TOWN OF LOS GATOS   |
|  | LANDSCAPE  | TYP   | TYPICAL   |
|  | LEFT TURN  |   | VALLEY TRANSPORTATION AUTHORITY   |
| _T   | LEFT TURN  | V I 🖯   | VALLET TRANSPORTATION ACTIONITY   |

**BENCHMARK** <u>PROJECT BENCHMARK –</u> SCVWD BENCHMARK NO. 226 BRASS DISK AT THE BACK OF SIDEWALK, AT THE EAST END OF THE NORTH GUARD RAIL; AT THE NORTHEAST CORNER OF LARK AVENUE BRIDGE OVER LOS GATOS ELEVATION = 277.78 FEET DATUM: NAVD 1988 MSL

BASIS OF BEARINGS: THE BEARING, NORTH 26° 19' 37"

EAST OF THE CENTERLINE OF WINCHESTER BOULEVARD, BETWEEN THE FOUND MONUMENTS AS SHOWN ON THAT CERTAIN PARCEL MAP, RECORDED IN BOOK 503 OF MAPS AT PAGE 37, SANTA CLARA COUNTY RECORDS, WAS USED AS THE BASIS OF ALL BEARINGS SHOWN ON

TOWN ENGINEER



SHEET INDEX

DEMOLITION PLAN - WINCHESTER BLVD

STREET IMPROVEMENT PLAN - WINCHESTER BLVD

STREET IMPROVEMENT PLAN - WINCHESTER BLVD

LARK AT WINCHESTER TRAFFIC SIGNAL MODIFICATION

WIMBLEDON AT WINCHESTER TRAFFIC SIGNAL MODIFICATION

**EXISTING** 

<u>TITLE</u>

TITLE SHEET

CENTER LINE

DRIVEWAY

PROPERTY LINE

EDGE OF PAVEMENT

ACCESSIBILITY RAMP

TRUNCATED DOMES

CONCRETE PAVEMENT

ASPHALT PAVEMENT

ASPHALT OVERLAY

STANDARD CITY MONUMENT

SLURRY SEAL

BENCH MARK

WATER METER

FIRE HYDRANT

STREET LIGHT

POWER POLE PULL BOX

ELECTRICAL LINE

IRRIGATION LINE

OVERHEAD LINE

NATURAL GAS LINE

STORM DRAIN LINE

TELEPHONE LINE

LIGHTING CONDUIT

WATER LINE

TREE/SHRUB

FENCE

<u>PPROVED BY TOWN OF LOS GATOS PUBLIC WORKS ENGINEERING</u>

LISA PETERSEN, RCE NO: 46792, EXPIRES 6/30/2015

SANITARY SEWER LINE

TRAFFIC SIGNAL CONDUIT

ROADSIDE SIGN & SIGN CODE

TREE PROTECTION FENCING

STORM DRAIN INLET

CABLE TELEVISION LINE

MANHOLE

STANDARD DETAILS

EXISTING SITE CONDITIONS

AND EQUIPMENT SCHEDULE

AND EQUIPMENT SCHEDULE

LARK AT WINCHESTER CONDUCTOR

WIMBLEDON AT WINCHESTER CONDUCTOR

WINCHESTER SIGNING AND STRIPING PLAN

**LEGEND** 

WINCHESTER STREET LIGHTING PLAN

BASMAA POLLUTION PREVENTION

#### SEAL OF ENGINEER OF WORK:

I HEREBY DECLARE THAT I AM THE ENGINEER OF WORK FOR THIS PROJECT, THAT I HAVE EXERCISED RESPONSIBLE CHARGE OVER THE DESIGN OF THE PROJECT AS DEFINED IN SECTION 6703 OF THE BUSINESS AND PROFESSIONS CODES, AND THAT THE DESIGN IS CONSISTENT WITH CURRENT STANDARDS.

UNDERSTAND THAT THE CHECK OF PROJECT DRAWINGS AND SPECIFICATIONS BY THE CITY OF MONTE SERENO IS CONFINED TO A REVIEW ONLY AND DOES NOT RELIEVE ME, AS ENGINEER OF WORK, OF MY RESPONSIBILITIES FOR PROJECT DESIGN.


ROBERT V. HENRY R.C.E. 60443 CARROLL ENGINEERING, INC.

SAN JOSE, CALIF. 95128

TELEPHONE: 408-261-9800

1101 SO. WINCHESTER BLVD., STE. H-184

▼ R1



**SHEET** 

C-1

C-4

TS-1

TS-2

TS-3

TS-4

TS-5

**PROPOSED** 

4 4 4

**▼** R1






HE

DATE 02/04/2015 SCALE AS SHOWN SHEET NO.

AUTHORIZED CHANGES & USES: The engineer preparing these plans will not be responsible for, or liable for, unauthorized changes to or uses of these plans. All changes to the plans must be in writing and must be approved by the preparer of these plans.




TOWN OF LOS GATOS


TOWN OF LOS GATOS


DATE
02/04/2015

SCALE
AS SHOWN

SHEET NO.










/MENTS **IMPRO** STREET

DATE 02/04/2015 SCALE AS SHOWN SHEET NO.








|                    | CON                     | IDUCTOR TABLE |           |     |      |              |             |  |  |  |  |
|--------------------|-------------------------|---------------|-----------|-----|------|--------------|-------------|--|--|--|--|
| A \ A \ C          |                         |               |           | F   | RUNS | 5            |             |  |  |  |  |
| AWG                | CIRCUIT                 | <u>/1\</u>    | ^<br>/2\_ | /3/ | 4    | / <u>5</u> \ | <u>/6</u> \ |  |  |  |  |
|                    | ø1                      |               |           |     |      |              |             |  |  |  |  |
|                    | <b>ø</b> 2              | 3             | 3         | 3   | 3    | 3            |             |  |  |  |  |
|                    | ø4                      | 3             | 3         | 3   | 3    | 3            |             |  |  |  |  |
|                    | ø5                      | 3             | 3         | 3   | 6    | 6            | 3           |  |  |  |  |
|                    | ø6                      |               |           |     | 3    | 3            | 3           |  |  |  |  |
|                    | ø8                      |               |           |     |      |              |             |  |  |  |  |
|                    | ø2P                     |               |           |     |      |              |             |  |  |  |  |
| NO                 | ø4P                     |               | 2         | 2   | 2    | 2            |             |  |  |  |  |
| NO.                | ø6P                     |               |           |     | 2    | 2            | 2           |  |  |  |  |
| 14                 | ø8P                     |               |           |     |      |              |             |  |  |  |  |
|                    | PPB(ø2P)                |               |           |     |      |              |             |  |  |  |  |
|                    | PPB(ø4P)                |               | 2         | 2   | 2    | 2            |             |  |  |  |  |
|                    | PPB(ø6P)                |               |           |     | 2    | 2            | 2           |  |  |  |  |
|                    | PPB(ø8P)                |               |           |     |      |              |             |  |  |  |  |
|                    | PPB COMMON              |               | 1         | 1   | 1    | 1            | 1           |  |  |  |  |
|                    | SPARES                  | 3             | 3         | 3   | 3    | 3            | 3           |  |  |  |  |
|                    | TOTAL No. 14            | 12            | 17        | 17  | 27   | 27           | 14          |  |  |  |  |
|                    | SIGNAL NEUTRAL          | 1             | 1         | 1   | 2    |              | 1           |  |  |  |  |
| NO.<br>8           | LUMINAIRE               | 2             | 2         | 2   | 2    |              |             |  |  |  |  |
| 0                  | TOTAL No. 8             | 3             | 3         | 3   | 4    |              | 1           |  |  |  |  |
| NO.<br>6           | SIGNAL                  |               |           |     |      | 2            |             |  |  |  |  |
| VIDEO<br>DETECTION | VIDEO/POWER<br>CABLES   | 1             | 2         | 2   | 3    |              |             |  |  |  |  |
| CABLES             | EMTRAC ANTENNA<br>CABLE |               |           |     | 1    |              |             |  |  |  |  |
|                    | FIRE STATION CABLE      |               |           |     | 1    |              |             |  |  |  |  |
|                    | TOTAL CABLES            |               |           |     | 2    |              |             |  |  |  |  |
| SIC                | SIGNAL<br>INTERCONNECT  |               |           |     |      |              |             |  |  |  |  |
| COND               | JIT SIZE (INCHES)       | 3"            | 3"        | 3"  | 2-3" | 2-3"         | 3"          |  |  |  |  |
|                    | N=NEW E=EXISTING        | Е             | Ε         | E   | N    | N            | E           |  |  |  |  |


INTERSECTION SHALL BE WIRED WITH ALL NEW CONDUCTOR/CABLES

| EQUIPMENT SCHEDULE |          |           |          |             |         |            |        |     |       |           |  |
|--------------------|----------|-----------|----------|-------------|---------|------------|--------|-----|-------|-----------|--|
| No.                | STANDARD |           |          | VEH SIG MTG |         | PED SIGNAL |        | PPB |       | HPS       | SPECIAL REQUIREMENTS   |
| NO.                | Туре     | Sig. M.A. | Lum.M.A. | Mast Arm    | Pole    | Ø          | MTG    | Ø   | ARROW | LUMINAIRE | SPECIAL REQUIREMENTS   |
| (A)                | 24-4-70  | 45'       | 12'      | MAT<br>MAS  | SV-2-TB | 1          | ı      | 1   | 1     | LED       | EXISTING R73-5 AND D3-1 (Lark Ave) ON SMA. EXISTING VIDEO CAMERA ON LMA TO REMAIN.             |
| (B)                | 16-2-70  | 20'       | _        | MAS         | SV-2-TB | 4          | SP-1-T | 4   | LEFT  | _         | EXISTING D3-1 (Winchester Blvd) AND VIDEO CAMERA ON SMA TO REMAIN.                             |
| (c)                | 19-3-70  | 30'       | 15'      | MAS         | SV-2-TB | 4<br>6     | SP-2-T | 4   | RIGHT | LED       | EXISTING VIDEO CAMERA ON LMA. EXISTING EMTRAC ANTENNA ON POLE. INSTALL D3-1 (Lark Ave) ON SMA. |
| (D)                | 1-B      | _         | _        | _           | TV-2-T  | 6          | SP-1-T | 6   | RIGHT | _         |  |

#### GENERAL NOTES (FOR SHEETS TS-1 THROUGH TS-5 ONLY)

- 1. ALL WORK AND MATERIALS SHALL CONFORM TO THE REQUIREMENTS OF THE 2010 STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION (CALTRANS) STANDARD PLANS AND STANDARD SPECIFICATION AND THE TOWN OF LOS GATOS STANDARDS.
- 2. A LIST OF MATERIALS PROPOSED BY THE CONTRACTOR TO BE USED ON THIS PROJECT FOR STREET LIGHTING AND/OR TRAFFIC SIGNALS INCLUDING, BUT NOT LIMITED TO, LUMINAIRES, POLES, CONDUIT, CONDUCTORS, PULL BOXES, GROUND RODS, SIGNAL EQUIPMENT AND SERVICE EQUIPMENT SHALL BE SUBMITTED TO THE CITY'S PROJECT INSPECTOR FOR APPROVAL PRIOR TO THE START OF WORK. THE LIST SHALL INCLUDE MANUFACTURER'S SPECIFICATIONS FOR ALL APPLICABLE PRODUCTS.
- 3. EXISTING ELECTRICAL SYSTEMS INCLUDING TRAFFIC SIGNALS, TRAFFIC VEHICLE AND PEDESTRIAN DETECTION FACILITIES, TRAFFIC SIGNAL COMMUNICATION AND MONITORING FACILITIES, STREET LIGHTING FACILITIES, FLASHING BEACONS AND SIGN ILLUMINATION FACILITIES, OR APPROVED TEMPORARY REPLACEMENTS THEREOF, SHALL BE KEPT IN EFFECTIVE OPERATION FOR THE BENEFIT OF THE TRAVELING PUBLIC DURING THE PROGRESS OF WORK, EXCEPT WHEN SHUTDOWN IS PERMITTED TO ALLOW FOR ALTERNATIVES OR FINAL REMOVAL OF THE SYSTEMS.
- 4. THE CONTRACTOR SHALL OBTAIN PERMITS NECESSARY TO PERFORM THE IMPROVEMENTS SHOWN IN THESE PLANS FROM THE APPROPRIATE AGENCIES AND SHALL COMPLY WITH THE AGENCIES REQUIREMENTS. THE CONTRACTOR SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE AND LOCAL LAWS.
- 5. THE CONTRACTOR SHALL REPAIR AND REPLACE EXISTING LANDSCAPING, IRRIGATION FACILITIES, CURBS, SIDEWALK, STRIPING, MARKINGS, PAVEMENT MARKERS, PRIVATE UTILITY AND FIBER OPTIC FACILITIES, ETC., DAMAGED BY CONTRACTORS OPERATIONS DURING CONSTRUCTION.
- 6. ALL UTILITIES AND IMPROVEMENTS THAT BECOME DAMAGED DURING CONSTRUCTION SHALL BE COMPLETELY RESTORED BY THE CONTRACTOR TO THE SATISFACTION OF THE TOWN ENGINEER.
- 7. CONTRACTOR SHALL BE RESPONSIBLE FOR DAMAGE INCURRED TO SERVICE LATERALS (GAS, WATER, ELECTRICAL, SEWER, ETC.) WHICH MAY OR MAY NOT BE SHOWN ON THESE PLANS. CONTRACTOR SHALL COORDINATE WITH UTILITY COMPANIES AND HAVE THEM MARK THE LATERALS.
- 8. CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROTECTION OF AND DAMAGE INCURRED DURING CONSTRUCTION TO ALL EXISTING OVERHEAD CABLES (ELECTRICAL, TELEPHONE AND CABLE TV) WHICH MAY OR MAY NOT BE SHOWN ON THESE PLANS. CONTRACTOR SHALL NOTIFY UTILITY COMPANIES PRIOR TO ANY WORK IN OVERHEAD LOCATIONS.
- 9. CONTRACTOR SHALL COORDINATE ANY ADJUSTMENT, REMOVAL, REPLACEMENT OR RELOCATION OF UNDERGROUND FACILITIES IN THE CONSTRUCTION AREA WITH THE UTILITY COMPANY.
- 10. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFICATION OF LOCATIONS AND DEPTHS OF EXISTING UTILITIES BEFORE BEGINNING CONSTRUCTION. UTILITY COMPANIES AND UNDERGROUND SERVICE ALERT (USA) (800–227–2600) SHALL BE NOTIFIED TWO FULL WORKING DAYS PRIOR TO EXCAVATION WITHIN THE PROJECT AREA.
- 11. ALL NEW SIGNAL HEADS SHALL BE 12" LENSES WITH BACKPLATES AND VISORS. SCREWS SHALL BE PLACED IN ALL BACK PLATE SCREW HOLES.
- 12. THE CONTRACTOR SHALL FURNISH AND INSTALL RED, YELLOW AND GREEN (CIRCULAR AND/OR ARROW) LIGHT EMITTING DIODE (LED) MODULES IN EACH NEW VEHICLE SIGNAL HEAD. THE LED SIGNAL MODULES SHALL BE GELCORE OR APPROVED EQUAL.
- 13. THE CONTRACTOR SHALL FURNISH AND INSTALL AN LED MODULE INCORPORATING A NUMERICAL COUNTDOWN DISPLAY IN COMBINATION WITH STANDARD LED PORTLAND ORANGE "UPRAISED HAND" AND LED WHITE "WALKING PERSON" SYMBOLS IN EACH NEW PEDESTRIAN SIGNAL HEAD. COUNTDOWN PEDESTRIAN SIGNAL MODULES SHALL CONFORM TO CURRENT CALTRANS SPECIFICATIONS.
- 14. THE CONTRACTOR SHALL FURNISH AND INSTALL A REMOVABLE METALLIC TUNNEL VISOR CONFORMING TO ANSI STANDARD D-10.1 ON ALL NEW VEHICLE SIGNAL SECTIONS. PLASTIC VISORS SHALL NOT BE USED.
- 15. ALL NEW SIGNAL AND LIGHTING STANDARDS SHALL HAVE A GALVANIZED FINISH AND SHALL NOT BE PAINTED.
- 16. NEW PEDESTRIAN PUSH BUTTON (PPB) UNITS SHALL BE ADA—COMPLIANT WITH AN ACTUATOR BUTTON A MINIMUM OF TWO INCHES IN DIAMETER. PUSH BUTTONS SHALL BE MOUNTED ON TRAFFIC SIGNAL POLES WITH ACTUATOR BUTTONS CENTERED AT AN ELEVATION 38 INCHES ABOVE THE ADJACENT WALKING SURFACE.
- 17. TRAFFIC CONTROL DURING CONSTRUCTION SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. ALL TRAFFIC CONTROL PLANS SHALL BE SUBMITTED TO THE TOWN OF LOS GATOS FOR REVIEW AND APPROVAL PRIOR TO USE. TWO WEEKS NOTICE IS REQUIRED AND A MINIMUM OF TWO UNIFORMED POLICE OFFICERS AS DETERMINED NECESSARY BY POLICE AND PAID FOR BY CONTRACTOR SHALL BE REQUIRED TO DIRECT TRAFFIC DURING SIGNAL SHUT DOWN PERIODS.
- 18. SIGNAL SHUT DOWNS SHALL BE LIMITED TO 9:00 AM TO 3:00 PM ON MONDAYS THROUGH FRIDAYS. CONTRACTOR SHALL CONTACT THE TOWN TWO DAYS PRIOR TO COMMENCEMENT OF ANY WORK REQUIRING SIGNAL SHUT DOWN.
- 19. ALL EQUIPMENT TO BE SALVAGED SHALL BE DELIVERED UNDAMAGED TO TOWN OF LOS GATOS SERVICE CENTER AT 41 MILES AVENUE. THE CONTRACTOR SHALL CONTACT THE TOWN OF LOS GATOS DEPARTMENT OF PARKS AND PUBLIC WORKS AT (408) 395-2859, FORTY-EIGHT (48) HOURS IN ADVANCE TO ARRANGE FOR ACCEPTANCE OF SALVAGED EQUIPMENT.
- 20. LOCATIONS OF CONTROLLER, STANDARDS, CONDUITS, PULL BOXES AND OTHER EQUIPMENT ARE APPROXIMATE AND WILL BE LOCATED IN THE FIELD AS DIRECTED BY THE ENGINEER.
- 21. THIS PLAN IS ACCURATE FOR ELECTRICAL WORK ONLY.
- 22. ALL NEW PULL BOXES SHALL BE NO. 5 UNLESS OTHERWISE NOTED. PULL BOXES SHALL HAVE A MAXIMUM SPACING OF 200'. ALL PULL BOXES WITH 4 OR MORE CONDUITS ENTERING SHALL BE NO. 6.
- 23. ALL CONDUIT SHALL BE 3" UNLESS OTHERWISE NOTED ON THE PLAN.
- 24. ALL DETECTION ZONES WILL BE PROGRAMMED AT TIME OF SIGNAL TURN ON.
- 25. ALL ABANDONED FOUNDATIONS SHALL BE KNOCKED DOWN TO TWO FEET BELOW SUBGRADE.
- 26. ALL ABANDONED CONDUITS SHALL BE HARD-CAPPED.







|           | CON                      | TA    | TABLE |    |    |            |    |  |  |  |  |
|-----------|--------------------------|-------|-------|----|----|------------|----|--|--|--|--|
| A VA / O  | 7                        | RUNS  |       |    |    |            |    |  |  |  |  |
| AWG       | CIRCUIT                  | ^<br> | ^     | 3  | 4  | <u>/5\</u> | 6  |  |  |  |  |
|           | ø1                       | 3     |       | 3  | 3  | 6          | 3  |  |  |  |  |
|           | ø2                       | 3     |       | 3  | 3  | 3          |    |  |  |  |  |
|           | <b>ø</b> 4               |       |       |    |    |            |    |  |  |  |  |
| -         | <u>ντ</u><br>ø5          |       |       |    |    |            |    |  |  |  |  |
| -         | ø6                       |       |       |    |    | 3          | 3  |  |  |  |  |
|           |                          |       |       |    |    |            |    |  |  |  |  |
|           | ø8                       |       | 3     | 3  | 3  | 6          | 3  |  |  |  |  |
| -         | ø2P                      | 2     |       | 2  | 2  | 2          |    |  |  |  |  |
|           | ø4P                      |       |       |    |    |            |    |  |  |  |  |
| NO.       | ø6P                      |       |       |    |    |            |    |  |  |  |  |
| 14        | ø8P                      | 2     |       | 2  | 2  | 4          | 2  |  |  |  |  |
| '         |                          | 2     |       | 2  | 2  | 2          |    |  |  |  |  |
|           | PPB(ø2P)<br>PPB(ø4P)     |       |       |    |    |            |    |  |  |  |  |
| -         | PPB(ø6P)                 |       |       |    |    |            |    |  |  |  |  |
|           | PPB(ø8P)                 | 2     |       | 2  | 2  | 4          | 2  |  |  |  |  |
| -         |                          |       |       |    |    | _          |    |  |  |  |  |
|           | PPB COMMON               | 1     |       | 1  | 1  | 2          | 1  |  |  |  |  |
| -         | IISNS<br>SPARES          | 3     |       | 3  | 3  | 6          | 3  |  |  |  |  |
| -         | 31 711123                |       |       |    |    |            |    |  |  |  |  |
|           |                          |       |       |    |    |            |    |  |  |  |  |
|           | TOTAL No. 14             | 18    | 3     | 21 | 21 | 38         | 17 |  |  |  |  |
| NO.       | SIGNAL NEUTRAL LUMINAIRE | 1     |       | 2  | 2  | 2 4        | 2  |  |  |  |  |
| 8         | LOMINAINL                |       |       |    |    |            |    |  |  |  |  |
|           | TOTAL No. 8              | 1     |       | 3  | 3  | 6          | 3  |  |  |  |  |
| OTHER     |                          |       |       |    |    |            |    |  |  |  |  |
| CABLES    | EMTRAC CABLE             |       |       |    |    | 1          | 1  |  |  |  |  |
| VIDEO     | VIDEO/POWER              |       |       | _  |    | _          |    |  |  |  |  |
| DETECTION | CABLES                   |       |       | 1  | 1  | 2          | 1  |  |  |  |  |
| -         |                          |       |       |    |    |            |    |  |  |  |  |
| DLC       | 40                       |       | 1     | 1  | 1  | 1          |    |  |  |  |  |
|           | ø8                       |       | 1     | 1  | 1  | 1          |    |  |  |  |  |
| -         |                          |       |       |    |    |            |    |  |  |  |  |
|           |                          |       |       |    |    |            |    |  |  |  |  |
|           |                          |       |       |    |    |            |    |  |  |  |  |
|           |                          |       |       |    |    |            |    |  |  |  |  |
|           |                          |       |       |    |    |            |    |  |  |  |  |
|           | SIGNAL                   |       |       |    |    |            |    |  |  |  |  |
| SIC       | INTERCONNECT             |       |       |    |    | 2          |    |  |  |  |  |
|           | JIT SIZE (INCHES)        | 3     | 2     | 4  | 4  | 2-3"       | 4  |  |  |  |  |
|           | N=NEW E=EXISTING         | Ε     | Ε     | N  | N  | Ε          | Ν  |  |  |  |  |


NOTE: THE CONTRACTOR SHALL REWIRE THE INTERSECTION WITH ALL NEW CONDUCTOR/CABLES


|              |           |           |          |                   | EQUIPN  | <b>JEI</b> | NT SC  | HE  | EQUIPMENT SCHEDULE |           |   |  |  |  |  |  |  |  |  |  |
|--------------|-----------|-----------|----------|-------------------|---------|------------|--------|-----|--------------------|-----------|---|--|--|--|--|--|--|--|--|--|
| No.          |           | STANDARD  |          | VEH SIG MTG       |         | PED SIGNAL |        | PPB |                    | HPS       | SPECIAL REQUIREMENTS  |  |  |  |  |  |  |  |  |  |
| 140.         | Туре      | Sig. M.A. | Lum.M.A. | Mast Arm          | Pole    | Ø          | MTG    | Ø   | ARROW              | LUMINAIRE |   |  |  |  |  |  |  |  |  |  |
| ( <u>A</u> ) | 19-3-70   | 30'       | 12'      | MAS               | SV-1-T  | 2          | SP-1-T | 2   | LEFT               | **/***    | EXISTING R3-18 AND D3-1 (Wimbledon Dr) ON SMA TO REMAIN. TOWN WILL FURNISH THE ITERIS EDGE 2 VIDEO DETECTION SYSTEM, CAMERA, MOUNTING BRACKETS AND POWER/VIDEO CABLES AND THE CONTRACTOR SHALL INSTALL.   |  |  |  |  |  |  |  |  |  |
| (B)          | 1-B       | 1         | 1        | _                 | TV-1-T  | _          | _      | ı   | _                  | _         |   |  |  |  |  |  |  |  |  |  |
| /            |           |           |          |                   |         | 2          |        | 2   | LEFT               | ded Adda  |   |  |  |  |  |  |  |  |  |  |
| (c)          | 1-B       | _         | _        | _                 | TV-2-T  | 8          | SP-2-T | 8   | RIGHT              | **/***    |   |  |  |  |  |  |  |  |  |  |
| D            | 29-5-100  | 50'       | 15'      | MAS<br>MAS<br>MAS | SV-2-TB | 8          | SP-1-T | 8   | LEFT               | ***       | INSTALL D3-1(Wimbledon Dr) ON SMA. RELOCATE THE EXISTING EMTRAC FIRE PREEMPTION ANTENNA FROM THE EXISTING POLE TO THIS NEW POLE. TOWN WILL FURNISH THE ITERIS EDGE 2 VIDEO DETECTION SYSTEM, CAMERA, MOUNTING BRACKETS AND POWER/VIDEO CABLES AND CONTRACTOR SHALL INSTALL. |  |  |  |  |  |  |  |  |  |
| E            | 1-B (10') | _         | _        | _                 | TV-1-T  | _          | _      | ı   | _                  | -         |   |  |  |  |  |  |  |  |  |  |
| F            | *         | _         | 15'      | _                 | SV-2-TB | _          | _      | _   | _                  | ***       |   |  |  |  |  |  |  |  |  |  |

- \* = TOWN STANDARD OCTAFLUTE STREET LIGHT POLE
- \*\* = SALVAGE THE EXISTING 200W HPS LUMINAIRES.
- \*\*\* = FURNISH AND INSTALL LED LUMINAIRE. LED LUMINAIRE SHALL BE LEOTECH EC3-10M-MV-NW-700.









#### STANDARD ELECTROLIER SPECIFICATIONS (OCTAFLUTE W/ LED LUMINAIRE)

Unless otherwise directed an octaflute street light pole shall meet the following specifications:

#### LED LUMINAIRE:

Beta or Leotech (or approved equal)

III Cut-Off Type: 240 volts Voltage:

70W HPS Equivalent (or as directed by Engineer) Wattage:

Photo Cell: Yes

#### POLE

MFG: Union Metal

401A-H-300-C2 Model 2C-30 Cat. No. Material: Galvanized Steel Octaflute

Gauge:

Finish: Galvanized (Not painted)

Pole Height: 30' Finish Height: 28'9" at pole 31'9" at head

Arm Length: 8'

#### FOUNDATION

See Foundation Detail.

#### WIRE

Size: #8 AWG min.

Type: Waterproof 2 pole fused splice connector rated 30A,

600V, with two (2) 10A fuses

Location: Pole base

NOT TO SCALE

STANDARD ELECTROLIER STD. PLAN NO. APPROVED BY SPECIFICATIONS (OCTAFLUTE W/ LED FIXTURE) TOWN ENGINEER

#### **GENERAL NOTES:**

SEE SHEET TS-2

- 1. INSTALL POLE TAGS ON THE STREET LIGHT POLES.
- 2. THE CONTRACTOR SHALL VERIFY STREET LIGHT CIRCUITS AND IDENTIFY EXISTING SERVICE POINTS AND REPORT TO ENGINEER PRIOR TO BEGINNING OF WORK.


#### LEGEND:


- AB ABANDON, IF APPLIED TO CONDUITS, REMOVE CONDUCTORS
- CC CONNECT NEW AND EXISTING CONDUIT, REMOVE EXISTING CONDUCTORS AND INSTALL CONDUCTORS AS INDICATED

RS REMOVE AND SALVAGE EQUIPMENT


SC SPLICE NEW TO EXISTING CONDUCTORS

BEFORE EXCAVATING CALL U.S.A. UNDERGROUND SERVICE ALERT 800-227-2600 TWO WORKING DAYS BEFORE ALL PLANNED WORK OPERATIONS






# Pollution Prevention — It's Part of the Plan



## Make sure your crews and subs do the job right!

Runoff from streets and other paved areas is a major source of pollution in San Francisco Bay. Construction activities can directly affect the health of the Bay unless contractors and crews plan ahead to keep dirt, debris, and other construction waste away from storm drains and local creeks. Following these guidelines will ensure your compliance with local ordinance requirements.



## Materials storage & spill cleanup

### Non-hazardous materials management

- ✓ Sand, dirt, and similar materials must be stored at least 10 feet from catch basins, and covered with a tarp during wet weather or when rain is forecast.
- ✓ Use (but don't overuse) reclaimed water for dust control as needed.
- ✓ Sweep streets and other paved areas daily. Do not wash down streets or work areas with water!
- ✓ Recycle all asphalt, concrete, and aggregate base material from demolition activities.
- ✓ Check dumpsters regularly for leaks and to make sure they don't overflow.

  Repair or replace leaking dumpsters promptly.

### Hazardous materials management

- ✓ Label all hazardous materials and hazardous wastes (such as pesticides, paints, thinners, solvents, fuel, oil, and antifreeze) in accordance with city, state, and federal regulations.
- ✓ Store hazardous materials and wastes in secondary containment and cover them during wet weather.
- ✓ Follow manufacturer's application instructions for hazardous materials and be careful not to use more than necessary. Do not apply chemicals outdoors when rain is forecast within 24 hours.
- ✓ Be sure to arrange for appropriate disposal of all hazardous wastes.

### Spill prevention and control

- ✓ Keep a stockpile of spill cleanup materials (rags, absorbents, etc.) available at the construction site at all times.
- ✓ When spills or leaks occur, contain them immediately and be particularly careful to prevent leaks and spills from reaching the gutter, street, or storm drain. Never wash spilled material into a gutter, street, storm drain, or creek!
- ✓ Report any hazardous materials spills immediately! Dial 911 or your local emergency response number.



- ✓ Fuel and maintain vehicles on site only in a bermed area or over a drip pan that is big enough to prevent runoff.
- ✓ If you must clean vehicles or equipment on site, clean with water only in a bermed area that will not allow rinsewater to run into gutters, streets, storm drains, or creeks.
- ✓ Do not clean vehicles or equipment on-site using soaps, solvents, degreasers, steam cleaning equipment, etc.



## Earthwork & contaminated soils

- ✓ Keep excavated soil on the site where it is least likely to collect in the street.

  Transfer to dump trucks should take place on the site, not in the street.
- ✓ Use hay bales, silt fences, or other control measures to minimize the flow of silt off the site.



- ✓ Avoid scheduling earth moving activities during the rainy season if possible. If grading activities during wet weather are allowed in your permit, be sure to implement all control measures necessary to prevent erosion.
- ✓ Mature vegetation is the best form of erosion control. Minimize disturbance to existing vegetation whenever possible.
- ✓ If you disturb a slope during construction, prevent erosion by securing the soil with erosion control fabric, or seed with fast-growing grasses as soon as possible. Place hay bales down-slope until soil is secure.
- ✓ If you suspect contamination (from site history, discoloration, odor, texture, abandoned underground tanks or pipes, or buried debris), call your local fire department for help in determining what testing should be done.
- ✓ Manage disposal of contaminated soil according to Fire Department instructions.

# Dewatering operations

- ✓ Reuse water for dust control, irrigation, or another on-site purpose to the greatest extent possible.
- ✓ Be sure to call your city's storm drain inspector before discharging water to a street, gutter, or storm drain. Filtration or diversion through a basin, tank, or sediment trap may be required.
- ✓ In areas of known contamination, testing is required prior to reuse or discharge of groundwater. Consult with the city inspector to determine what testing to do and to interpret results. Contaminated groundwater must be treated or hauled off-site for proper disposal.

## Saw cutting

- ✓ Always completely cover or barricade storm drain inlets when saw cutting. Use filter fabric, hay bales, sand bags, or fine gravel dams to keep slurry out of the storm drain system.
- ✓ Shovel, absorb, or vacuum saw-cut slurry and pick up all waste as soon as you are finished in one location or at the end of each work day (whichever is sooner!).
- ✓ If saw cut slurry enters a catch basin, clean it up immediately.

## Paving/asphalt work



- ✓ Do not pave during wet weather or when rain is forecast.
- ✓ Always cover storm drain inlets and manholes when paving or applying seal coat, tack coat, slurry seal, or fog seal.
- ✓ Place drip pans or absorbent material under paving equipment when not in use.
- ✓ Protect gutters, ditches, and drainage courses with hay bales, sand bags, or earthen berms.
- ✓ Do not sweep or wash down excess sand from sand sealing into gutters, storm drains, or creeks. Collect sand and return it to the stockpile, or dispose of it as trash.
- ✓ Do not use water to wash down fresh asphalt concrete pavement.

# Concrete, grout, and mortar storage & waste disposal

- ✓ Be sure to store concrete, grout, and mortar under cover and away from drainage areas. These materials must never reach a storm drain.
- ✓ Wash out concrete equipment/trucks off-site or designate an on-site area for washing where water will flow onto dirt or into a temporary pit in a dirt area. Let the water seep into the soil and dispose of hardened concrete with trash.



- ✓ Divert water from washing exposed aggregate concrete to a dirt area where it will not run into a gutter, street, or storm drain.
- If a suitable dirt area is not available, collect the wash water and remove it for appropriate disposal off site.

## Painting

- ✓ Never rinse paint brushes or materials in a gutter or street!
- ✓ Paint out excess water-based paint before rinsing brushes, rollers, or containers in a sink. If you can't use a sink, direct wash water to a dirt area and spade it in.
- ✓ Paint out excess oil-based paint before cleaning brushes in thinner.
- ✓ Filter paint thinners and solvents for reuse whenever possible Dispose of oil-based paint sludge and unusable thinner as hazardous waste.

Bay Area Stormwater Management
Agencies Association (RASMAA)
1-888-BAYWISE


Storm drain polluters may be liable for fines of up to \$10,000 per day!

BEC 2/6/14 TOWN COMMENTS

RVH 11/20/14 TOWN COMMENTS

RVH 12/05/14 TOWN COMMENTS

ADDUCTOR SAN JOSE, CA 95128
FAX: 408-261-9800
FAX: 408-261-0595
E-MAIL: Bryce@carroll-engineering.o



IAA POLUTION PREVENTION TOWN OF LOS GATOS

> DATE 12/20/2013 SCALE AS SHOWN

> > EC-1